

# Datasheet

## Geomis



### Product Description

Designed with both style and function in mind, this decorative bollard houses a polycarbonate diffuser and stepped louvre to give an elegant, symmetrical distribution.


### Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 44.0 lm/W and will be capable of producing up to 1,105 luminaire lumens at 4000K with a CRI >70. It shall have a radial distribution and is rated at IP65 and IK08.

### Specification

Weight: 6.7kg  
 Material: Die-cast Aluminium  
 Paint finish: RAL7016 Anthracite Grey  
 Marine Grade Finish

### Optics



Radial

### Key Features

- 25W
- 1,105 Luminaire Lumens
- Efficacy up to 44.0 lm/W
- 4000K, CRI >70
- Lifetime >50,000hr, L80



### Mounting Options

- Flange Mount

### Other Options

- Photocell Option  
[Contact for details](#)

Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included	Driver Type
GEO25KGF	25.0	1,105	1200	Radial	4000	IP65	IK08	6.7	Marine Grade RAL 7016 Anthracite Grey	Driver Inc	Fixed



## Dimensions

