

Datasheet

Compass

Product Description

This sleek luminaire is ideal for illuminating any urban or street environment. Available in post top, catenary, suspended and wall mounted versions, Compass is perfect for creating a harmonious scheme on site.

Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 140.0 lm/W and will be capable of producing up to 19,590 luminaire lumens at 4000K with a CRI >70. It shall have asymmetric optics and is rated at IP66 and IK08.

Specification

Weight: 10.5 - 13.5kg

Windage: Artelys 350: 0.05 - 0.25m²

Artelys 460: 0.06 - 0.32m²

Material: Die-cast Aluminium Paint finish: Graphite Grey

Key Features

- 28.0W 152.0W
- 3,490 19,590 Luminaire Lumens
- Efficiency up to 140.0 Im/W
- 4000K, CRI >70
- Lifetime >100,000hr, L90









Mounting Options

- Post Top 60-76mm
- 48 60mm Side Entry Fixing

Other Options

- Colour Temperature Options
- Marine + Finish
 Contact for details

Optics





STU-W

kingfisherlighting.com
KF ALFRESCO URBAN

Code	Power	Luminaire Lumens	Drive Current	Optic	CCT(K)	IP	IK	Weight kg	Paint Finish	Driver Included
COM1TP-STU-W-4.5- 1M1F	28.0	3,490	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.4- 2M1F	45.1	5,660	400	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.5- 2M1F	53.0	6,880	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.4- 3M1F	62.0	8,460	400	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.5- 3M1F	78.0	10,200	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.4- 4M1F	81.0	11,210	400	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM1TP-STU-W-4.5- 4M1F	104.0	13,510	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	11	Graphite Grey Finish	Driver inc
COM2TP-STU-W-4.4- 5M1F	100.0	13,960	400	Street Optic - Narrow (STU-W)	4000	IP66	IK08	14	Graphite Grey Finish	Driver inc
COM2TP-STU-W-4.5- 5M1F	128.0	16,610	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	14	Graphite Grey Finish	Driver inc
COM2TP-STU-W-4.4- 6M1F	119.0	16,490	400	Street Optic - Narrow (STU-W)	4000	IP66	IK08	14	Graphite Grey Finish	Driver inc
COM2TP-STU-W-4.5- 6M1F	152.0	19,590	500	Street Optic - Narrow (STU-W)	4000	IP66	IK08	14	Graphite Grey Finish	Driver inc

Dimensions









